



IP CAMERA HS-T087SL

- H.265 / H.264 / MJPEG
- 2MP (1920 × 1080)
- 10~ 20 M IR night view distance
- 3D DNR, DWDR, HLC, BLC, defog
- ICR auto switch, true day / night
- Support ROI coding
- Support smart phone, iPad, remote monitoring
- IP67 ingress protection
- Intelligent analytics: abnormal video signal detection, line crossing detection and region intrusion detection

RoHS **CE** **FC**





HS-T087SL

Camera	
Image Sensor	1 / 3.2 " CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 25 s ~ 1 / 100,000 s
Min. Illumination	0.012 lux@F1.2,AGC ON; 0 lux with IR 0.046 lux@F2.0,AGC ON; 0 lux with IR
Lens	Board 2.8 mm @F2.0
Horizontal view Angle	93.7°
IR Distance	10~20 m
WDR	Digital WDR
Day & Night	ICR auto switch
BLC	YES
HLC	YES
Defog	YES
Digital DNR	3D DNR
Angle Adjustment	Pan: 0° ~360° ; Tilt:0° ~80° ; Rotation: 0° ~360°
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1 (704 × 480), 480 × 240, CIF (352 × 240)
Main Stream (S1)	1080P / 720P @30fps
Sub Stream (S2)	D1 / CIF @30fps
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen,NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Audio	
Audio Compression	-
Two-way audio	-
Interfaces	
Network	RJ45
Video Output	-
Audio line in	-
Audio line out	-
Alarm Input	-
Alarm Output	-
Storage	
SD card	-
Network remote storage	Yes
Hardware Reset	-

Functions		
Remote Monitoring	Web browsing,CMS remote control	
Online Connection	Support simultaneous monitoring for up to 3 users Support multi-stream real time transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS	
Interface Protocol	ONVIF	
Smart Alarm	Motion detection	
Intelligent Analytics	Exception,Line Crossing,Intrusion	
General function	Watermark, video mask, heartbeat, password protection	
PoE	Yes	
Others		
Power Supply	DC12V / PoE	
Power Consumption	< 5W	
Operating Environment	- 20 ° C ~ 55 ° C (-4° F~131° F) Humidity: less than 95 % (non-condensing)	
Dimensions	Φ 74.5 × 167.5 mm	
Weight	Approx. 240g	
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)	
Ingress Protection	IP67	
Accessories		
B627	B640	B639
B615	B616	B628